

Catalog Number: GAA50BFC4AAGGAXX73

UPC Number: 88861402321

Status: Active

Abbreviated Switchgear, System Type 3 Phase/3 Wire, Bus Type Silver Plated with No Insluation, Main Bus Rating 5000A, Vertical Bus Rating 3,200A, Section Type Feeder, Short Circuit Rating 65kA, System Voltage 480V (508V Maximum), Compartment A Instrument Compartment, Compartment B Instrument Compartment, Compartment C E3 1600A Frame, Compartment D E3 1600A Frame, Enclosure Type Type 1, Door Option No Doors, Connection Options None, Section Depth 72 Inches, Section Width 30 Inches

North American Specifications (UNSPSC)	
UNSPSC	39121116 Low voltage switchgear
IGCC	4374 Low voltage switchgear
Brand Name	ABB
Туре	Emax Link
Special Features	Barriers between the bus compartment and the ca-
	ble compartment for increased personnel protection
Bus Rating	5000A
Short Circuit Rating	65kA
Size	92 Inches x 72 Inches x 30 Inches
Insulation	No Insulation
Enclosure	Type 1
Phase	3

Packaging	
Outer Quantity	1
Outer Dimensions (inches)	72x30x92
Weight Uom	2194 lbs. Each

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com

Thomas & Betts - USA