



### Main

|              |                                |
|--------------|--------------------------------|
| Product Type | Industrial Control Transformer |
| Type         | T                              |

### Complementary

|                                |  |
|--------------------------------|--|
| Number of Phases               | 1 phase  |
| Power Rating                   | 250 VA UL<br>250 VA CSA<br>250 VA NOM<br>160 VA CE |
| Primary to Secondary Voltage   | 480 V 240 V<br>460 V 230 V<br>440 V 220 V          |
| Temperature Rise               | 80 °C  |
| Electrical Connection          | Screw clamp terminals                              |
| Height                         | 3.25 in (82.55 mm)                                 |
| Width                          | 3.75 in (95.25 mm)                                 |
| Depth                          | 5.25 in (133.35 mm)                                |
| Material                       | Copper: winding                                    |
| Fingersafe Cover Compatibility | FSC2   |

### Environment

|                        |  |
|------------------------|--|
| Certifications         | CSA file LR37055 guide 184-N-90[RETURN]UL listed file E61239 |
| Enclosure Type         | Not rated (open device)                                      |
| Insulation Temperature | 266 °F (130 °C)  |

### Ordering and shipping details

|                   |                           |
|-------------------|---------------------------|
| Category          | 16206-9070 T (NOT TF) MTO |
| Discount Schedule | CP8                       |
| GTIN              | 785901328056              |
| Returnability     | No                        |
| Country of origin | US                        |

## Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Number of Units in Package 1 | 1                      |
| Package 1 Height             | 5.60 in (14.224 cm)    |
| Package 1 Width              | 6.40 in (16.256 cm)    |
| Package 1 Length             | 7.20 in (18.288 cm)    |
| Package 1 Weight             | 7.40 lb(US) (3.357 kg) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Compliant with Exemptions   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | No need of specific recycling operations  |
| PVC free                   | Yes   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|