



Powering Business Worldwide

pe.eaton.com



H-Max Drive

HMX040B4NAP3L3

UPC:786685563756

Dimensions:

- **Height:** 13.67 IN
- **Length:** 45.45 IN
- **Width:** 11.44 IN

Weight:125 LB

Notes:All boards are varnished. Corrosion resistant.
Battery included in all drives for real-time clock.
Keypad kit includes HOA bypass. Keypad kit includes HOA, back reset for Europe application.
EMI/RFI filters included. DC link choke included.

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Brake Chopper:** No brake chopper
- **Options:** Fused drive isolation, Pilot lights
- **Amperage Rating:** 40A
- **Enclosure:** IntelliDisconnect NEMA Type 12
- **Frame Size:** 6
- **Horsepower:** 30 hp
- **Software:** A
- **Voltage Rating:** 480V

Supporting documents:

- [Variable frequency drive - Product overview](#)
- [Eatons Volume 6-Solid-State Motor Control](#)
- [Size B Oversize Type 1, 12 and 3R Enclosure Outline Dims](#)
- [Eaton H-Max HVAC Drives](#)
- [Eaton Specification Sheet - HMX040B4NAP3L3](#)

Certifications:

- IEC 61800-5-1
- cUL Certified
- UL 508C
- EN 61800-5-1

Product compliance:

- CE Marked