

GROUND ROD CLAMP, U-BOLT, TINNED, ONE CONDUCTOR, 2/0 SOL-250 KCMIL STR, 70 MM² STR-120 MM² STR CONDUCTOR SIZE, UL

CATALOG NUMBER

GC065



CERTIFICATIONS



FEATURES

Tinned finish provides a theft-deterrent appearance

Accepts conductors in both parallel and perpendicular orientations

PRODUCT ATTRIBUTES

Material: Bronze;Stainless Steel 304 (EN 1.4301)


Finish: Tinned

Ground Rod Diameter, Nominal: 5/8" - 3/4"

Conductor Size, UL: 2/0 Sol - 250 kcmil Str;70 mm² Str - 120 mm² Str

Conductor Orientation (Parallel or Perpendicular)								
GC064	Conducto	Conductor Size						
Nominal Ground Rod Diameter	#4 Sol	#4 Str	#2 Sol	#2 Str	1/0 Sol		1/0 Str-3/0 Sol	
5/8" copper-bonded ground rod	Par.	Par.	Par.	Par.	Both		Perp.	
5/8" galvanized/stainless steel ground rod	Par.	Par.	Par.	-	Perp.		Perp.	
3/4" copper-bonded ground rod	Par.	-	-	-	Perp.		Perp.	
3/4" galvanized/stainless steel ground rod	-	-	-	-	Perp.		-	
GC065	Conducto	Conductor Size						
Nominal Ground Rod Diameter	#4 Sol-#4 Str		#2 Sol-4/0 Sol			4/0 Str	250 kcmil Str	
5/8" copper-bonded ground rod	Par.	Par.		Both		Both	Par.	
5/8" galvanized/stainless steel ground rod	Par.	Par.		Both			Par.	
3/4" copper-bonded ground rod	Par.	Par.		Both			-	
3/4" galvanized/stainless steel ground rod	Par.	Par.		Both			-	

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

A WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to-www.P65Warnings.ca.gov.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands: **nVent.com** CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.

3