

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

1200652252

Status:

Active

Overview:

Brad M8 and M12 Cordsets with Knurled Hexnuts and WSOR Cable

Description:

Micro-Change (M12) Single-Ended Cordset with Knurled Hexnut, 4 Poles, Female (Straight) to Pigtail, 22 AWG, Unshielded WSOR Cable, 2.0m (6.56') Length

|                               |                                                      |
|-------------------------------|------------------------------------------------------|
| Documents:                    |                                                      |
| <a href="#">Drawing (PDF)</a> | <a href="#">RoHS Certificate of Compliance (PDF)</a> |

|                               |                                                              |
|-------------------------------|--------------------------------------------------------------|
| Agency Certification          |                                                              |
| UL                            | E152210                                                      |
| General                       |                                                              |
| Product Family                | Industrial Cordsets                                          |
| Series                        | 120065                                                       |
| Connector End A               | Micro-Change (M12)                                           |
| Connector End B               | Pigtail                                                      |
| IP Rating                     | IP67                                                         |
| Material - Contact            | Brass                                                        |
| Overview                      | Brad M8 and M12 Cordsets with Knurled Hexnuts and WSOR Cable |
| Product Name                  | Micro-Change (M12)                                           |
| Protocol                      | N/A                                                          |
| Region                        | Europe                                                       |
| Type                          | Single Ended                                                 |
| UPC                           | 887191554662                                                 |
| Physical                      |                                                              |
| Cable Diameter                | 5.10mm (.201")                                               |
| Cable Length                  | 2.0m (6.56')                                                 |
| Color - Cable Jacket          | Black                                                        |
| Coupling Style                | Knurled Hexnut, Threaded                                     |
| Gender                        | Female-Pigtail                                               |
| Keyway                        | Single                                                       |
| LED Indicator                 | No                                                           |
| Material - Cable Jacket       | TPU                                                          |
| Material - Connector Body     | TPU                                                          |
| Material - Coupling Nut       | Nickel-plated Brass                                          |
| Material - Plating Mating     | Gold                                                         |
| Net Weight                    | 89.989/g                                                     |
| Orientation                   | Straight to Pigtail                                          |
| Poles                         | 4                                                            |
| Temperature Range - Operating | -25°C to +85°C                                               |
| Wire Size AWG                 | 22                                                           |
| Wire/Cable Type               | WSOR                                                         |
| Electrical                    |                                                              |
| Current - Maximum per Contact | 4.0A                                                         |
| Voltage - Maximum             | 250V                                                         |
| Material Info                 |                                                              |
| Engineering Number            | 804000B30M020                                                |
| Reference - Drawing Numbers   |                                                              |
| Sales Drawing                 | 1200652251-00P                                               |



Series image - Reference only

|                                                               |               |
|---------------------------------------------------------------|---------------|
| EU ELV                                                        |               |
| Not Relevant                                                  |               |
| EU RoHS                                                       | China RoHS    |
| Compliant with Exemption 6(c)                                 |               |
| REACH SVHC                                                    |               |
| Contained Per - D(2020)9139-DC (19 Jan 2021)                  |               |
| lead                                                          |               |
| Halogen-Free                                                  |               |
| Status                                                        |               |
| Not Low-Halogen                                               |               |
| For more information, please visit <a href="#">Contact US</a> |               |
| China ROHS                                                    | 50 Image      |
| ELV                                                           | Not Relevant  |
| RoHS Phthalates                                               | Not Contained |

Search Parts in this Series

120065 Series

This document was generated on 03/02/2021

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**