



*Powering Business Worldwide*

[pe.eaton.com](http://pe.eaton.com)

## K-Factor Non Linear Transformer, Ventilated

**H29R28T22CUEE**

**UPC:**786685198026

### Dimensions:

- **Height:** 62.18 IN
- **Length:** 30.68 IN
- **Width:** 31.44 IN

**Weight:**2271 LB

**Notes:**NEMA TP-1 efficient

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Special Features:** Electrostatically Shielded
- **Design:** K-4
- **Coil Material:** Copper windings
- **Frame:** 918A
- **Frequency Rating:** 60 Hz
- **Phase:** Three-phase
- **Primary Voltage:** 208V
- **Secondary Voltage:** 208Y/120V
- **Tap Size:** 1 at +5% FCAN, 2 at -5% FCBN
- **Temperature Rating:** 150°C
- **Volt Ampere Rating:** 225 KVA
- **Weathershield:** WS34

### Supporting documents:

- [Eatons Volume 2-Commercial Distribution](#)
- [Eaton Specification Sheet - H29R28T22CUEE](#)

### Certifications:

- UL Listed



**Product compliance:**

- NEMA TP-1 Compliant

---

© 2016 Eaton. All rights reserved.