

Product data sheet

Characteristics

HVL415BGL

Switchgear, HVL, single, 600A, 15kV, 10E to 400E boric acid fuse, transformer disconnect, left, NEMA 1



Main

Product	Transformer Disconnect
Not Included	Fuse to be ordered separately
Device application	Transformer left side

Complementary

Protection type	Fuse boric acid
Associated fuse rating	10 A E 15 A E 20 A E 25 A E 30 A E 40 A E 50 A E 65 A E 80 A E 100 A E 125 A E 150 A E 175 A E 200 A E 250 A E 300 A E 400 A E
Line Rated Current	600 A
Momentary Amperes Asymmetrical	40 kA
Full Load Current	300 A
Frequency	50/60 Hz
Number of Poles	3P
[Ur] highest voltage for equipment	15 kV
Basic Insulation Level	95 kV
Enclosure Rating	NEMA 1
Electrical Connection	Lugs
Wire Gauge	AWG 2...600 kcmil aluminium/copper
Enclosure Width	38 in (965.20 mm)
Enclosure Depth	54.5 in (1384.30 mm)
Enclosure Height	90 in (2286.00 mm)

Environment

Product Certifications	UL Listed[RETURN]cUL
------------------------	----------------------

Ordering and shipping details

Category	07944-15KV DIGEST HVL NEMA 1
Discount Schedule	PE5A
GTIN	3606486276501
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1200.00 lb(US) (544.311 kg)

Contractual warranty

Warranty	18 months
----------	-----------