


Double-Ended Cordsets
BCC A323-A313-70-345-VX43W6-150
Order Code: BCC09C2

BALLUFF



4MT5
(CYJV CABLE ASSEMBLY)



Electrical connection

Cable	PVC Yellow, 15.00 m
Cable diameter D	10.24 mm $\pm$ 0.20 mm
Conductor cross-section	16 AWG
Connection 1	7/8"-Female, angled, 3-pin
Connection 2	7/8"-Male, straight, 3-pin
Number of conductors	3
System	Molded/Molded

Electrical data

Cable rated voltage AC max.	600 V
Cable rated voltage DC max.	600 V
Operating voltage Ub	300 VDC / 300 VAC
Rated current (40 °C)	13.0 A

Environmental conditions

Cable temperature, fixed routing	-40...105 °C
IP rating	IP67, IP68/IP67, IP68

Remarks

Bulk cable: PVC UL listing, 16/3 ST00W/Male00W CSA FT2 105°C 600 V
Enclosure rating per IEC 60529, only in screwed state with the associated mating piece.

General data

Approval/Conformity	cULus EAC WEEE
---------------------	----------------------


Material

Cable jacket, material	PVC
Material contact carrier	PUR/PUR
Material contacts	Brass/Brass
Material cover nut	Die-cast zinc/Die-cast zinc
Material grip	PUR/PUR

Mechanical data

Cable jacket, color	yellow
Cable length L	15.00 m
Tightening torque pigtail	1.5 Nm/1.5 Nm

Connector Drawings



Wiring Diagrams

