



Powering Business Worldwide

pe.eaton.com

Eaton FERRUPS UPS

FG010CC2H1A0A0B

UPC:743172081766

Dimensions:

- **Height:** 25 IN
- **Length:** 25 IN
- **Width:** 18 IN

Weight:367 LB

Warranties:

- 2 year

Specifications:

- **Special Features:** AVR/DVR (recommended for PFC loads)
- **Type:** UPS
- **Input Connection:** 5-20P
- **Input Cord Length:** 6 ft
- **Input Voltage Range:** 120V
- **Input Frequency Range:** 60 Hz
- **Input Power Factor:** 0.98
- **Receptacle:** (4) 5-20R, (1) L5-20R
- **Output Waveform:** Sine wave
- **Output Voltage Range:** $\pm 3\%$ for input voltages of +15 to -20%
- **Battery Form Factor:** ERT internal battery, standard charger
- **Communication:** RS-232 (DB-25)
- **Software Compatibility:** Intelligent Power Software Suite
- **User Interface:** On/off switch, alarm switch, 5 front indicator lights
- **Relative Humidity:** 5-90% non-condensing
- **Temperature Range:** 0° to 40°C (32° to 104°F)

Supporting documents:

- [Eaton Specification Sheet](#) -



FG010CC2H1A0A0B

Certifications:

- ANSI/IEEE Std C62.45
- FCC Cat. A
- IEC 801-5
- IEC 801-2
- IEC 801-4
- ANSI/IEEE Std C62.41
- UL Listed
- CSA Certified

Product compliance: No Data