

AV In-Wall Enclosure
15A, 125V, 2-Gang
Recessed TR Duplex Receptacle with Cable Pass Thru

HUBBELL

Features

- Tamper-Resistant (TR) duplex
- Easily mounts to a box
- Cable pass thru organizes and protects low voltage cables

Ordering Information

Description	Device Color	UPC	Catalog Number
Smooth face, back and side wired.	Ivory	88377830582	RR1512I

Listings


UL Listed to UL 498
CSA Certified 22.2, No. 42

Specifications

Pass Thru Brushes	Nylon
Face	Nylon
Base	PVC
Power Contacts	.030 in. (.8mm) Brass
Ground Contacts	.014 in. (.35mm) Brass
Terminal Screws	Plated Steel
Automatic Self-grounding Staple	Stainless steel
Mounting Screws	Zinc Plated Steel

Performance

Electrical	
Current Interrupting	Certified for current interrupting at full rated current
Dielectric Voltage	Withstands 1,500V minimum
Mechanical	
Product Identification	Ratings are a permanent part of the device
Terminal Accommodation	#14-12 AWG stranded or solid copper conductor only
Terminal Identification	Terminals identified in accordance with UL 498 and CSA
Environmental	
Flammability	UL 94 V-2
Operating Temperatures	Maximum continuous 75°C; minimum -40°C (w/o impact)



Accessories

Gangable AV Wall Box	HBL985
Recessed TR AV Plastic Box	RR1500

Online Resources

Customer Use Drawing
eCatalog
Installation Instructions

