



PILOT LIGHTS



Pilot Light



Illuminated Button

Class I, Div. 1 & 2, Groups B, C, D^④
 Class I, Zones 1 & 2, Groups IIB, IIA
 Class II, Div. 1 & 2, Groups E, F, G
 Class III
 NEMA 3, 4, 4X, 7 (B, C, D) 9 (E, F, G)

See Area Classification Chart
 page C62 for Details



LISTED - File E12379



Certified - File LR11714

See files for details or call Killark.

FEATURES-SPECIFICATIONS

G PILOT LIGHTS					
CATALOG NUMBER ^①			COLOR	CONTACT TYPE ^③	NAMEPLATE MARKING ^②
SHORT ^④	LONG	EXTENDED			
G023-A23C	GOB3-A23C N34	GOL3A	AMBER	110-120 VOLTS FULL VOLTS	BLANK
G023-B23C	GOB3-B23C N34	GOL3B	BLUE		BLANK
G023-C23C	GOB3-C23C N34	GOL3C	CLEAR		BLANK
G023-F23C	GOB3-F23C N34	GOL3F	FROSTED		BLANK
G023-G23C	GOB3-G23C N34	GOL3G	GREEN		BLANK
G023-R23C	GOB3-R23C N34	GOL3R	RED		BLANK

G PILOT LIGHTS WITH LED 110 VOLT LAMPS					
—	GOB3-A23C N34 LED	GOL3A LED	AMBER	110-120 VOLTS FULL VOLTS (LED)	BLANK
—	GOB3-G23C N34 LED	GOL3G LED	GREEN		BLANK
—	GOB3-R23C N34 LED	GOL3R LED	RED		BLANK

G ILLUMINATED BUTTON OR PUSH TO TEST PILOT LIGHT					
—	GOB4-A233C N34	GOL4A3	AMBER	110-120 VOLTS FULL VOLTS	BLANK
—	GOB4-B233C N34	GOL4B3	BLUE		BLANK
—	GOB4-C233C N34	GOL4C3	CLEAR		BLANK
—	GOB4-F233C N34	GOL4F3	FROSTED		BLANK
—	GOB4-G233C N34	GOL4G3	GREEN		BLANK
—	GOB4-R233C N34	GOL4R3	RED		BLANK
—	GOB4-A230C N34	GOL4A	AMBER	110-120 VOLTS NO CONTACT BLOCKS	BLANK
—	GOB4-B230C N34	GOL4B	BLUE		BLANK
—	GOB4-C230C N34	GOL4C	CLEAR		BLANK
—	GOB4-F230C N34	GOL4F	FROSTED		BLANK
—	GOB4-G230C N34	GOL4G	GREEN		BLANK
—	GOB4-R230C N34	GOL4R	RED		BLANK

G ILLUMINATED BUTTON OR PUSH TO TEST PILOT LIGHT WITH LED 110 VOLT LAMPS					
—	GOB4-A233C N34 LED	GOL4A3 LED	AMBER	110-120 VOLTS FULL VOLTS (LED)	BLANK
—	GOB4-G233C N34 LED	GOL4G3 LED	GREEN		BLANK
—	GOB4-R233C N34 LED	GOL4R3 LED	RED		BLANK
—	GOB4-A230C N34 LED	GOL4A LED	AMBER	110-120 VOLTS (LED) NO CONTACT BLOCKS	BLANK
—	GOB4-G230C N34 LED	GOL4G LED	GREEN		BLANK
—	GOB4-R230C N34 LED	GOL4R LED	RED		BLANK

^① Refer to catalog page C62 to select proper operator for enclosure, pages C70 & C71 for accessories, page C62 for complete details on Area Classification of operators, page C74 for Dimensional information.

^② Nameplates are double sided.

^③ Contact Blocks are shown in their normal position.

^④ Short style operators are suitable for Class I Group C & D, Class II Group E, F, G and cULus only.



PILOT LIGHTS FOR ATEX / CENELEC APPLICATIONS



Pilot Light ATEX



Illuminated Push Button ATEX

Class I, Div. 1 & 2, Groups B, C, D
 Class I, Zones 1 & 2, Groups IIB+H₂, IIA
 Class II, Div. 1 & 2, Groups E, F, G
 Class III
 NEMA 3, 4, 4X, 7 (B, C, D) 9 (E, F, G)
 ATEX-EEcd IIB + H2

UL LISTED - File E12379

SP® Certified - File LR11714

Ex PTB No. 03ATEX 1203 U

FEATURES-SPECIFICATIONS

G PILOT LIGHTS				
CATALOG NUMBER ^①		COLOR	CONTACT TYPE ^③	NAME PLATE MARKING ^②
LONG	EXTENDED			
GOB3-A23C N34CN	GOL3ACN	AMBER	 110-120 VOLTS FULL VOLTS	BLANK
GOB3-B23C N34CN	GOL3BCN	BLUE		BLANK
GOB3-C23C N34CN	GOL3CCN	CLEAR		BLANK
GOB3-F23C N34CN	GOL3FCN	FROSTED		BLANK
GOB3-G23C N34CN	GOL3GCN	GREEN		BLANK
GOB3-R23C N34CN	GOL3RCN	RED		BLANK
G PILOT LIGHTS WITH LED 110 VOLT LAMPS				
GOB3-A23C N34LEDCN	GOL3ALEDCN	AMBER	 110-120 VOLTS FULL VOLTS (LED)	BLANK
GOB3-G23C N34LEDCN	GOL3GLEDCN	GREEN		BLANK
GOB3-R23C N34LEDCN	GOL3RLEDCN	RED		BLANK
G ILLUMINATED PUSH BUTTON OR PUSH TO TEST PILOT LIGHT				
GOB4-A233CN34CN	GOL4A3CN	AMBER	 110-120 VOLTS FULL VOLTS	BLANK
GOB4-B233CN34CN	GOL4B3CN	BLUE		BLANK
GOB4-C233CN34CN	GOL4C3CN	CLEAR		BLANK
GOB4-F233CN34CN	GOL4F3CN	FROSTED		BLANK
GOB4-G233CN34CN	GOL4G3CN	GREEN		BLANK
GOB4-R233CN34CN	GOL4R3CN	RED		BLANK
GOB4-A230CN34CN	GOL4A0CN	AMBER	 110-120 VOLTS NO CONTACT BLOCKS	BLANK
GOB4-B230CN34CN	GOL4B0CN	BLUE		BLANK
GOB4-C230CN34CN	GOL4C0CN	CLEAR		BLANK
GOB4-F230CN34CN	GOL4F0CN	FROSTED		BLANK
GOB4-G230CN34CN	GOL4G0CN	GREEN		BLANK
GOB4-R230CN34CN	GOL4R0CN	RED		BLANK
G ILLUMINATED PUSH BUTTON OR PUSH TO TEST PILOT LIGHT WITH LED 110 VOLT LAMPS				
GOB4-A233CN34LEDCN	GOL4A3LEDCN	AMBER	 110-120 VOLTS FULL VOLTS (LED)	BLANK
GOB4-G233CN34LEDCN	GOL4G3LEDCN	GREEN		BLANK
GOB4-R233CN34LEDCN	GOL4R3LEDCN	RED		BLANK
GOB4-A230CN34LEDCN	GOL4A0LEDCN	AMBER	 110-120 VOLTS (LED) NO CONTACT BLOCKS	BLANK
GOB4-G230CN34LEDCN	GOL4G0LEDCN	GREEN		BLANK
GOB4-R230CN34LEDCN	GOL4R0LEDCN	RED		BLANK

^① Refer to catalog page C62 to select proper operator for enclosure, pages C70 & C71 for accessories, page C62 for complete details on Area Classification of operators, page C74 for Dimensional information.

^② Nameplates are double sided.

^③ Contact Blocks are shown in their normal position.

NOTE: British standards BSEN50014 and EN50018 have special marking and relamping demands that require modifications to the standard Killark Pilot Lights. Pilots lights and illuminated push buttons on this page must be used for enclosures that are modified to meet ATEX/CENELEC.