



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## CE Marked Control Transformer

**CE0075E4CCEFS**

**UPC:**786680040795

### Dimensions:

- **Height:** X
- **Length:** X
- **Width:** X

**Notes:**Epoxy encapsulated, Laminations of high quality silicon steel to minimize core losses and optimize performance, 50/60Hz operation, 130°C insulation system standard, Molded-in terminals, Non-short circuit-proof

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Coil Material:** Copper windings
- **Design:** MTE
- **Modification 1:** Factory-mounted finger-safe terminal shields
- **Primary Voltage:** 550/575/600V
- **Secondary Voltage:** 110/115/120V
- **Tap Size:** None
- **Temperature Rating:** 55°C
- **Type:** CE Marked Control Transformer
- **Volt Ampere Rating:** 75 VA

### Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [Eaton Specification Sheet - CE0075E4CCEFS](#)

### Certifications:

- cUL Certified



- UL Listed
- CSA Certified
- IEC 61558-2

**Product compliance:**

- RoHS Compliant

---

© 2016 Eaton. All rights reserved.