



H-Max Drive

HMX9D632NAP3L4

UPC:786685567235

Dimensions:

Height: 10.36 INLength: 30 INWidth: 7.88 IN

Weight:48 LB

Notes:All boards are varnished. Corrosion resistant. Battery included in all drives for real-time clock. Keypad kit includes HOA bypass. Keypad kit includes HOA, back reset for Europe application. EMI/RFI filters included. DC link choke included.

Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

• Brake Chopper: No brake chopper

• Options: Fused drive isolation, Pilot lights

Amperage Rating: 9.6A

• Enclosure: IntelliPass NEMA Type 1

Frame Size: 4Horsepower: 3 hp

• Software: A

• Voltage Rating: 230V

Supporting documents:

- Variable frequency drive Product overview
- Eatons Volume 6-Solid-State Motor Control
- Eaton H-Max HVAC Drives
- Eaton Specification Sheet HMX9D632NAP3L4

Certifications:

• UL 508C



- cUL Certified
- IEC 61800-5-1
- EN 61800-5-1

Product compliance:

• CE Marked

© 2016 Eaton. All rights reserved.