

 Catalog Number:
 EXN04MMC2K

 Product ID:
 7TCA297180R0406

 UPC Number:
 78621019832

 EAN Number:
 05011949235236

Status: Active

Single Compression Cable Gland, M20 Thread, For Use with Non-Armoured Cable, Flame-proof Ex d and Increased Safety Ex e, IP66-68 Rating, Length 40mm, Cable Range 4 to 12mm, Kit with Locknut, Shroud, Earth Tag, and Washer, Nickel Plated Brass

| <b>North American Specifications</b> | (UNSPSC)   |
|--------------------------------------|--|
| UNSPSC                               | 39121431 Cable gland connector   |
| IGCC                                 | 4601 Cable gland connector   |
| Brand Name                           | Kopex  |
| Туре                                 | Single Compression Cable Gland   |
| Special Features                     | Kit Comes with Locknut, Shroud, Earth Tag, and Washer  |
| Application                          | For Use with Unarmoured Cable to Provide Secure Cable Connections Through Knockouts and Threaded Entries |
| Standard                             | UL Listed, Approved to EN60079-0, 60079-1, 60079-7, 60079-31   |
| Size                                 | M20  |
| Conductor Range                      | 4 to 12 Millimeters  |
| Material                             | Brass  |
| Finish                               | Nickel Plated  |
| Color                                | Metallic   |
| Insulation                           | IP66-68 Rating   |
| Temperature Rating                   | -40 to 80 Degrees C  |
| Environmental Conditions             | Flameproof Ex d and Increased Safety Ex e  |

| European Specifications (ETIM)       |                            |
|--------------------------------------|----------------------------|
| ETIM                                 | EC000441 Cable screw gland |
| Thread type                          | Metric                     |
| Nominal thread size metric/PG        | 20                         |
| Pitch thread                         | 1.5mm                      |
| Thread length                        | 16mm                       |
| Hexagon angular dimension            | 24.5mm                     |
| Suitable for cable diameter          | 4.0-12.0mm                 |
| Material                             | Metal                      |
| Material quality                     | Brass                      |
| Surface protection                   | Nickel-plated              |
| Halogen free                         | N                          |
| Glass-fibre reinforced               | N                          |
| Degree of protection (IP)            | IP68                       |
| Shock resistant                      | N                          |
| Colour                               | Natural colour             |
| Bend radius protection/trumpet flare | N                          |
| With locknut                         | Υ                          |
| Model                                | Straight                   |
| Flat cable coupling                  | N                          |
| Strain relief                        | N                          |
| Operating temperature                | -40-+80°C                  |
| Explosion-tested version             | Υ                          |
| For Ex-zone gas                      | None                       |
| For Ex-Zone dust                     | None                       |
| EMC-version                          | N                          |



| Packaging                 |                  |
|---------------------------|------------------|
| Inner Quantity            | 1                |
| Inner Dimensions (inches) | .39x5.71x5.91    |
| Outer Quantity            | 100              |
| Outer Dimensions (inches) | 7.87x15.75x11.02 |
| Weight Uom                | 0.38 lbs. Each   |

## For further technical assistance, please contact us...

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com