



## Alternate Catalog No. PSR16-600-11 Catalog No. 1SFA896107R1100

Description: "PSR SSTR,600V/24V AC/DC,15.2A"

UPC No 7320500477182

Home > Soft Starters > Softstarter - Open (PSR)

**PSR softstarter - The compact range**The PSR softstarter range is a simple yet reliable starting solution that utilizes only the most basic of soft starting features: soft start and stop. It performs well in applications requiring many starts per hour and is perfect for installations where you need to save space. **Main benefits\*** Small and compact starting solution\* Can perform many starts per hour\* Reduce energy loss at full speed with built-in bypass. **Main features\*** Rated operational current: 3 to 105 A\* Operational voltage: 208-600 V AC\* Control supply voltage: 24 V AC/DC or 100-240 V AC.

Descriptors	
Category	Softstarter - Open (PSR)
Specifications	
Product Type	Soft Starters
Input Voltage	208-600 V
Control Voltage	24Vac/dc
Normat Duty: Output Current (A)	15.2
Normal Duty: Motor Power (HP) at 460V	10
Power Dissipation In Watts	20.5
Height (Inches)	5.5
Width (Inches)	1.8
Depth (Inches)	4.5
Classifications	
RoHS Indicator	Yes
UL/CUL Listing	Yes
Dimensions	
Weight (lb)	0.99
Height (mm)	140
Width (mm)	45
Depth (mm)	113.5
Weight (kg)	0.45

electrification.us.abb.com Created on: 03/23/2024

electrification.us.abb.com Created on: 03/23/2024