

Catalog Number: Z4LEUFAK82NE0FFFK0EA
UPC Number: 88861450484
Status: Active

Emax2, Frame E4.2, Breaking Capacity UL 125/150kA @ 508VAC, Frame Rating UL 1600A, Rating Plug UL 800A, Drawout (Less Cradle), Trip Unit Hi-Touch-LSIG, Measuring Pro and Power Supply 110-240V AC/DC, Communication Modules Single MOD-RS-485, Combo Link and 2K, Auxiliary Contacts 6 Aux (400V) and 4 Aux (400V), Closing Coil 120-127V AC/DC, Shunt Trip 120-127V AC/DC, Undervoltage 120-127V AC/DC, Spring Charge Motor with Standard Aux and Actuator 100-130V AC/DC, PLP Padlock, Mechanical Operation Counter

North American Specifications (UNSPSC)

UNSPSC	39121601 Circuit breakers
IGCC	4813 Circuit breakers
Brand Name	ABB
Sub Brand	Emax 2
Frame	E4.2
Number Of Poles	3
Auxiliary Contacts	6 AUX (400V)
Height	13.03 in ; 331 mm
Operating Temperature	40 Degrees C/104 Degrees F

Packaging

Outer Quantity	1
Outer Dimensions (inches)	24.213x20.276x23.622
Weight Uom	178.59 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com