


**INSULATED BUSHINGS****Insulated Bushings Malleable Iron**  
N/A**B41**

Catalog #: 1129

**APPLICATIONS**For use on threaded rigid/IMC conduit to provide a smooth rounded surface at the entrance of raceways  
N/A**PRODUCT FEATURES**Insuliner temperature rated at 150 degrees Celsius  
Malleable iron construction insures mechanical protection for the raceway  
Zinc electro plated for added corrosion protection  
1/2 in. to 1 in. trade sizes are also available in die cast zinc**UL LISTED**

Standard 514B, UL Listed E195969

**CSA**

C22.2 No. 18

**GENERAL PRODUCT INFORMATION**

Trade Size: 4 in.

**DRAWING DIMENSIONS**Dimension A: 4-29/32 in.  
Dimension B: 15/16 in.  
Dimension C: 3-55/64 in.**PACKAGING**Package Type: Carton  
Ship Carton Qty.: 5  
Product UPC-A Labeled: No  
Weight (Lbs. Per/C): 107.00  
Ship Carton Length (in.): 8.25  
Ship Carton Width (in.): 6.00  
Ship Carton Height (in.): 5.50  
Ctn Weight (Lbs.): 5.35  
UPC Number: 050169011294  
I2of5: 50050169011299