QOB325VH1021

Mini circuit breaker, QO, 25A, 3 pole, 120/240VAC, 22kA, bolt on mount, AC shunt





Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	25 A
Voltage Rating	120/240 V AC 240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	3P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Pressure plate
Options	Shunt trip 120/208/240 V AC

Complementary

o ompromortally		
Interrupt Rating	22 KA 120/240 V AC 50/60 Hz 22 KA 240 V AC 50/60 Hz 22 kA 120 V AC 50/60 Hz	
Number of Panel Spaces	4	
Wire Size	AWG 14AWG 8 copper or aluminium	
Tightening Torque	40.71 lbf.in (4.6 N.m)	
Height	2.99 in (76 mm)	
Width	2.99 in (76 mm)	
Depth	2.91 in (74 mm)	
Net Weight	1.21 lb(US) (0.549 kg)	

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	00015-QOB CIRCUIT BREAKERS
Discount Schedule	DE2
GTIN	3606486145555
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.20 in (8.128 cm)	
Package 1 Width	3.60 in (9.144 cm)	
Package 1 Length	4.70 in (11.938 cm)	
Package 1 Weight	19.36 oz (548.847 g)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☐ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty 18 months
