

# Rittal – The System.

Faster – better – everywhere.

## System Window for TS, SE – FT 2736.500

Date : Jan 22, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# System Window for TS, SE – FT 2736.500

created: 22.01.2017 build on [www.rittal.com/us-en](http://www.rittal.com/us-en)



## Product description

<b>Description:</b>	Utilized to cover display and operating instruments or cut-outs, and provide protection from dirt and moisture as well as unauthorized access.
<b>Benefits:</b>	<p>Base frame: Easily screw-fastened to the door thanks to modified dimensions (tubular door frame may be used as a drilling template).</p> <p>Base frame: Readily height-adjustable.</p> <p>Base frame: Stabilizes the door cut-out.</p> <p>Base frame: Conceals the cut edge.</p> <p>Base frame: The rain canopy prevents dirt from landing on the seal, protects the glass from being lifted out, prevents the ingress of dirt and moisture when opening the window.</p> <p>Base frame: Frame section height 30 mm or 60 mm</p> <p>Viewing window: Made from single-pane safety glass: High level of resistance to solvents and scratches, anti-static, reduced risk of injury if broken.</p> <p>Viewing window: Hinge with 180° opening angle, easily inserted.</p>
<b>Material:</b>	Extruded aluminum section with die-cast zinc corner pieces and single-pane safety glass.
<b>Surface finish:</b>	Base frame: Powder coated on the outside in RAL 7035, Hinge and lock section: Natural-anodized
<b>Protection category IP to IEC 60 529:</b>	IP 54
<b>Mounting tip:</b>	Standard double-bit lock insert may be exchanged for lock inserts 27 mm, type A, and/or for lock system Ergoform-S (except H = 270 mm).

## Product features

<b>Version:</b>	60 section
<b>Suitable for:</b>	Enclosure type: TS 8 Enclosure type: SE

Width: 800 mm (31 ")

<b>Dimensions:</b>	Height: 670 mm (26 ") Width: 700 mm (28 ") Depth: 77 mm (3 ")
<b>Viewing area:</b>	Height: 598 mm (24 ") Width: 563 mm (22 ")
<b>Build depth for components (max.):</b>	63 mm (2.5 ")
<b>Packaging unit:</b>	1 pc(s).
<b>Weight/packaging unit:</b>	8.65 kg (19.1 lb.)
<b>EAN:</b>	4028177476479
<b>Customs tariff number:</b>	76101000
<b>ETIM 6.0:</b>	EC002527
<b>ETIM 5.0:</b>	EC002527
<b>eCl@ss 8.0/8.1:</b>	27182301
<b>eCl@ss 7.0/7.1:</b>	27182301
<b>eCl@ss 6.0/6.1:</b>	27182301
<b>eCl@ss 5.1/5.1.4:</b>	27182301
<b>Approvals</b>	
<b>Certificates:</b>	EAC