



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Eaton H-Max variable frequency drive

**HMX9D6A2NAPEP3L3**

**UPC:**786685566337

### Dimensions:

- **Height:** 10.36 IN
- **Length:** 30 IN
- **Width:** 7.88 IN

**Weight:**48 LB

**Notes:**All boards are varnished. Corrosion resistant.  
Battery included in all drives for real-time clock.  
Keypad kit includes HOA bypass. Keypad kit includes HOA, back reset for Europe application.  
EMI/RFI filters included. DC link choke included.

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Brake Chopper:** No brake chopper
- **Options:** Output contractor, Fused drive isolation, Pilot lights
- **Amperage Rating:** 9.60A
- **Enclosure:** IntelliDisconnect NEMA Type 1
- **Frame Size:** FR4
- **Horsepower:** 3 hp
- **Software:** A
- **Voltage Rating:** 230 V

### Supporting documents:

- [Variable frequency drive - Product overview](#)
- [Eatons Volume 6-Solid-State Motor Control](#)
- [Size A Oversize Type 1, 12 and 3R Enclosure Outline Dims](#)



- [Eaton H-Max HVAC Drives](#)
- [Eaton Specification Sheet - HMX9D6A2NAPEP3L3](#)

**Certifications:**

- UL 508C
- EN 61800-5-1
- cUL Certified
- IEC 61800-5-1

**Product compliance:**

- CE Marked