EDB16060

Mini circuit breaker, E-Frame, 60A, 1 pole, 600Y/347 VAC, 25 kA max, bolt on



Main

Range of Product	125 A Frame EDB-EGB-EJB
Product or Component Type	Circuit-breaker
Device short name	EDB
Module type	E-Frame
Trip unit rating	1800 A

Complementary

Complementary	
Line Rated Current	60 A
Maximum operating voltage	600Y/347 V AC
AWG gauge	AWG 12AWG 2/0 aluminium AWG 14AWG 2/0 copper
Breaking capacity	14 kA 600Y/347 V AC
Circuit breaker application	HACR rated
Electrical connection	Lugs aluminium
Holding Current	630 A
Local signalling	Trip indicator
Mounting Mode	Bolt-on
Number of poles	1
Number of spaces	1
Number of spaces required	1
Product destination	NF panelboard
Protection Type	Overload Short-circuit
Trip unit technology	Thermal-magnetic
Breaking capacity code	D
Tightening torque	34.52 Lbf.In (3.9 N.m) 0.000.01 in² (2.56 mm²) (AWG 14AWG 10) 49.56 lbf.in (5.6 N.m) 0.020.11 in² (1070 mm²) (AWG 8AWG 2/0)
Height	5.66 in (143.76 mm)
Width	0.98 in (24.89 mm)
Depth	4.05 in (102.87 mm)
Net Weight	2 lb(US) (0.91 kg)

Environment

Product Certifications	IEC[RETURN]cULus
Ambient Air Temperature for Operation	104 °F (40 °C)

Ordering and shipping details

00931-EDB CIRCUIT BREAKERS
DE2
3606486143322
Yes
MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.67 in (14.4 cm)
Package 1 Width	0.98 in (2.5 cm)
Package 1 Length	4.06 in (10.3 cm)
Package 1 Weight	20.81 oz (590.0 g)

Offer Sustainability

REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
China RoHS Declaration
€Yes

Contractual warranty

Warranty	18 months
----------	-----------