



Powering Business Worldwide

pe.eaton.com

Eaton Type MTE industrial control transformer

C0250E3CFBNXXRT

UPC:786680001536

Dimensions:

- **Height:** X
- **Length:** X
- **Width:** X

Notes: Epoxy encapsulated, Laminations of high quality silicon steel to minimize core losses and optimize performance, 50/60Hz operation, 130°C insulation system standard, Molded-in terminals for maximum durability

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Coil Material:** Copper windings
- **Design:** MTE
- **Modification 1:** Factory-mounted 2-pole primary fuse block for non-rejection type fuses
- **Modification 2:** No secondary fuse clips
- **Modification 3:** Ring type terminals for connection to fuse block
- **Primary Voltage:** 230/460/575V
- **Secondary Voltage:** 115/95V
- **Tap Size:** None
- **Temperature Rating:** 55°C
- **Type:** Industrial Control Transformer
- **Volt Ampere Rating:** 250 VA

Supporting documents:

- [Industrial control transformers brochure](#)
- [dry-type distribution transformer-flex center line](#)



[card](#)

- [Transformer distribution catalog, volume 2, tab 2](#)
- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [Transformer consulting application guide](#)
- [Eaton Specification Sheet - C0250E3CFBNXXRT](#)

Certifications:

- UL Listed
- CSA Certified
- cUL Certified

Product compliance:

- RoHS Compliant