

Product data sheet

Characteristics

8538SDASP6

NEMA combination starter, Type S, 60A fusible disconnect, Size 2, 45A, 25HP at 600VAC, 3 phase, 3 pole, Motor Logic SSOLR, 120VAC coil, NEMA 12



Main

Product	Combination Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Starter Type	Non reversing
Line Rated Current	45 A
Number of Poles	3P
Horsepower Rating	25 Hp 460 V AC, 3 phase 25 hp 575 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Units	Selector switch HAND-OFF-AUTO)
Pilot Light	Red indicator on LED Green indicator off LED
Auxiliary Contacts	2 NO + 2 NC
Thermal overload type	Solid state Motor Logic class 10/20 15...45 A
Disconnect Type	Fusible disconnect switch H and K, 60 A, electrical SPDT
NEMA size	2
Height	27.75 in (704.85 mm)
Depth	9.59 in (243.59 mm)
Width	10.5 in (266.70 mm)

Environment

Enclosure Type	NEMA 12 painted sheet steel with external reset
Product Certifications	CSA[RETURN]UL Listed



Ordering and shipping details

Category	21213-8538,39 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901908524
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.28 in (31.2 cm)
Package 1 Width	14.02 in (35.6 cm)
Package 1 Length	32.28 in (82.0 cm)
Package 1 Weight	49.03 lb(US) (22.24 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------