



Representative Image

**Catalog No. THN3365J****Description: 400A 3P HD N5/12 600V NONFUSE****UPC No 783164087178****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty**

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. THN3365J

**Descriptors**

Category	Heavy Duty
GO Schedule	S1

**Specifications**

Voltage	600 AC
Amperage	400 A
Poles	3
Wires	3
Fusing	No Fuse
Enclosure	NEMA 5, 12 Drip/Dust-tight
Options	None
Wire Range (Cu/Al)	(1) 2-600 or (2) 1/0-250
240 Vac, NEC Std, 3-ph	125.0 hp
480 Vac, NEC Std, 3-ph	250.0 hp
600 Vac, NEC Std, 3-ph	350.0 hp
250 Vdc	50.0 hp
GSA Compliance	Yes

**Classifications**

cUL Listed	Yes
UL Listed	Yes

**Dimensions**

Height	48.0 in
Depth	7.9 in
Width	24.5 in
Weight	164.0 lb

  
**by ABB**

