

Flexible and Durable Activations for Multiple Systems

525 Series Service Fittings provide an expanded range of services to include audio/video devices. 525 Series Service Fittings' four-piece design delivers the flexibility of interchangeable faceplates and the durability to withstand multiple moves, adds and changes. These fittings can be applied to Walkerdut® Pro Series, Walkerdut® Underfloor Duct, Flushduct® and Walker 800 Series Floor Boxes.

525 Series Service Fittings are made from die-cast aluminum with a brushed satin finish. Each pedestal provides a single service, with multiple fittings required for two or more services. This line of fittings is ideal for use in schools, commercial office spaces and in labs.














525 Series Fittings provide single service wiring solutions.









FEATURES & BENEFITS

- **All 525 Series Fittings are UL Listed to U.S. and Canadian underfloor duct safety standards.**
- **Enlarged baseplate openings.** Two openings in the baseplate have been enlarged to accept 11/4" [32mm] locking nipple. Third opening accepts 1" [25mm] locking nipple. Provides greater wiring capacity.
- **Unique 3-position baseplate.** Allows fitting to be centered or adjusted 3/4" [19.1mm] to one side of center. This integral flexibility permits the fitting to be placed clear of furniture, equipment or adjacent fittings.
- **Interchangeable faceplates.** The 525 Series uses the same faceplates as the previous 505 Series four-piece fittings. Functional changes are now as simple as changing faceplates instead of entire activations.
- **A/V compatibility.** Accepts Extron® Electronics and Ortronics® audio/video devices.
- **Die-cast aluminum with satin finish.** Durable construction provides a fitting that performs and maintains a good appearance after years of service.
- **Flexible four-piece design.** Accommodates two removable faceplates. Choices include blank, power and communication styles. Reduces labor cost for making moves and changes.
- **New housing design.** Reduces the amount of visible lines and angles, improving aesthetic impact.
- **Datacom connectivity options.** Accepts industry standard and proprietary devices from a wide range of manufacturers to provide a seamless and aesthetically pleasing interface for voice, data, audio, and video applications at the point of use.









Four-Piece Service Fittings

Catalog No./Item	Description/Specifications	Catalog No./Item	Description/Specifications
525A	 Service Fitting – 1" [25mm] I.D. grommet one side.	525H	 Service Fitting – 20A, 125V duplex receptacle, one side.
525B	 Service Fitting – 1" [25mm] I.D. grommet both sides.	525I	 Service Fitting – 20A, 125V duplex receptacle, both sides.
525C	 Service Fitting – 1 1/4" [32mm] I.D. grommet one side.	525J	 Service Fitting – Decora or GFI receptacle opening, one side.
525D	 Service Fitting – 1 1/4" [32mm] I.D. grommet both sides.	525RT	 Service Fitting – Includes faceplate with opening, one side. Ortronics Series II and TracJack adapters included.
525F	 Service Fitting – Duplex receptacle opening, one side.	525ACT	 Service Fitting – Includes faceplate with opening, one side. Activate CM-MAB adapter included.
525G	 Service Fitting – Duplex receptacle opening, both sides		

525 Series Accessories

Catalog No./Item	Description/Specifications	Catalog No./Item	Description/Specifications																						
500RT	 Faceplate – Single opening. Ortronics Series II and TracJack adapters included.	500SP-	 Faceplate – Single opening. Suffix indicates hole diameter. <table><tr><th>SUFFIX</th><th>HOLE DIAMETER</th></tr><tr><td>1/2</td><td>1/2" [12.7mm]</td></tr><tr><td>7/8</td><td>7/8" [22.2mm]</td></tr><tr><td>1.0625</td><td>1.0625" [27mm]</td></tr><tr><td>1 1/8</td><td>1 1/8" [29mm]</td></tr><tr><td>1.39</td><td>1.39" [35mm]</td></tr><tr><td>1 7/16</td><td>1 7/16" [37mm]</td></tr><tr><td>1 1/2</td><td>1 1/2" [38mm]</td></tr><tr><td>1 9/16</td><td>1 9/16" [40mm]</td></tr><tr><td>1 5/8</td><td>1 5/8" [41mm]</td></tr><tr><td>2</td><td>2" [51mm]</td></tr></table>	SUFFIX	HOLE DIAMETER	1/2	1/2" [12.7mm]	7/8	7/8" [22.2mm]	1.0625	1.0625" [27mm]	1 1/8	1 1/8" [29mm]	1.39	1.39" [35mm]	1 7/16	1 7/16" [37mm]	1 1/2	1 1/2" [38mm]	1 9/16	1 9/16" [40mm]	1 5/8	1 5/8" [41mm]	2	2" [51mm]
SUFFIX	HOLE DIAMETER																								
1/2	1/2" [12.7mm]																								
7/8	7/8" [22.2mm]																								
1.0625	1.0625" [27mm]																								
1 1/8	1 1/8" [29mm]																								
1.39	1.39" [35mm]																								
1 7/16	1 7/16" [37mm]																								
1 1/2	1 1/2" [38mm]																								
1 9/16	1 9/16" [40mm]																								
1 5/8	1 5/8" [41mm]																								
2	2" [51mm]																								
500ACT	 Faceplate – Single opening. Activate CM-MAB adapter included.	500DR	 Faceplate – For single duplex receptacle.																						
500B	 Faceplate – Blank.	500-GFI	 Faceplate – For Decora or GFI device.																						
500-MAAP	 Faceplate – Accepts Extron® Electronics MAAP device plates.	525HB	 Housing and Base Plate –Only.																						
500T	 Faceplate – 1" [25mm] I.D. grommeted hole.																								

Activation Accessories

Catalog No./Item	Description/Specifications	Catalog No./Item	Description/Specifications
436-2 -7/8 [22.2mm] -11/2 [38mm] -2 [51mm] -23/8 [60mm] -3 [76mm] 	Afterset Inserts for Duct – 2" [51mm] IPS. 2 1/2" [64mm] core drill size; 2 1/4" [57mm] hole saw size. Suffix denotes height.	825SFCK 	Conversion Kit – To attach service fitting to 800 Series floor boxes. Includes 825C Ring, 1124L-1 Locking Nipple, and 825P-1 Adapter.
424 -3/4 [19.1mm] -1 [25mm] 	Extensions – For 2" [51mm] IPS preset or afterset inserts. Suffix denotes height of extension.	430S505 	Single Trim Plate – To attach fitting to Walkerdut Pro Series Preset. Base of 525 fitting not needed.
1126A-1/4 [6.4mm] -3/4 [19.1mm] -1 [25mm] -11/4 [32mm] -11/2 [38mm] 	Adapter – To change 2" [51mm] IPS preset or afterset to reduced opening size. Suffix denotes opening size.	431D505 	Double Trim Plate – To attach two fittings to Walkerdut Pro Series Presets. Base of 525 fitting not needed.
1124 -1 [25mm] 1124L -1 [25mm] 	Locking Nipple – For 1" [25mm] IPS opening; 1" [25mm] long. Locking Nipple – For 1" [38mm] IPS opening; 1 1/2" [38mm] long.	428B525 	Flush Carpet Plate – To attach to Walkerdut Pro Series Plate. Includes hardware.
1124-11/4 [38mm] 1124L -11/4 [38mm] 	Locking Nipple – For 1 1/4" [32mm] IPS opening; 1" [25mm] long. Locking Nipple – For 1 1/4" [32mm] IPS opening; 1 1/2" [38mm] long.		
1124F-1 [25mm] 	Locking Nipple – For 1" [25mm] IPS opening; 5/8" [16mm] long. For use on Flushduct Infloor Raceway.		
455F-1 	Outlet Flange – For 1 5/8" [241mm] diameter opening on Flushduct Infloor Raceway. Accepts 1" [25mm] locking nipple.		
1044B For 3/4" IPS 1044S 1045B For 1" IPS 1045S 1046B For 1 1/4" IPS 1046S 1043B For 2" IPS 1043S	Blanking Plates – 3 1/2" [89mm] diameter top plate  NOTE: B - Brass S - Stainless Steel		

Cross Reference

OLD CATALOG NUMBER	NEW CATALOG NUMBER
505A, 501E	525A
505ACT	525ACT
505B, 502E	525B
505C, 503E	525C
505F	525F
505G	525G
505H, 523E	525H
505HB	525HB
505I	525I
505J	525J
505RT	525RT



Electrical Wiring Systems

60 Woodlawn Street
West Hartford, CT 06110
Phone: 1.877.BY.LEGRAND (295-3472)
www.legrand.us

570 Applewood Crescent
Vaughan, Ontario L4K 4B4
Phone: 905.738.9195
www.legrand.ca

