

TSF REPLACEMENT MODULE, 275 VAC

CATALOG NUMBER

TSF240MTDS



CERTIFICATIONS



FEATURES

Replacement module for Transient Surge Filter

PRODUCT ATTRIBUTES

Nominal System Voltage (Un): 220 - 240 VAC

Max Continuous Operating Voltage (Uc): 275 VAC

Nominal Discharge Current (I_n): 3 kA 8/20 μs

Enclosure Material: UL® 94V-0 Thermoplastic

Temperature: -40 to 176 °F

Module Width: 1 M


Depth: 1.920"

Height: 1.780"

Width: 0.710"

Unit Weight: 0.150 lb

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER