

Catalog Number: T8VBD3GC0EACEEXX
UPC Number: 80432553651
Status: Active

TMAX Breaker frame size T8, 2000A, 3 pole, long time, short time and instantaneous protection functions, very high 125kA @ 480V breaking capacity, 110-120 VAC/DC closing coil, 4 auxiliary contacts (supplied as standard for breakers with PR332 trip units), 100-130 VAC/DC spring charging motor, 110-120 VAC/DC shunt trip, 110-120 VAC/DC undervoltage - second shunt trip, Underwriters Laboratories (sold in the US)

North American Specifications (UNSPSC)

UNSPSC	39121616 Molded case circuit breakers
IGCC	4927 Molded case circuit breakers
Brand Name	ABB
Sub Brand	Tmax
Type	Molded case circuit breaker
Standard	UL 489, CSA, IEC 60947-2
Current Rating	2000 (3P)
Trip Type	PR331/P-T8-LSI
Interrupt Rating	Very High
Auxiliary Contacts	4 aux contacts; (supplied as standard for breakers with PR332 trip units)

Packaging

Outer Quantity	1
Outer Dimensions (inches)	27.362x20.669x18.701
Weight Uom	196.01 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com