



### Catalog No. TG3326R

Description: 600A 3P GD N3R 240V FUSIBLE SW

UPC No 783164008609

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > General Duty

Designed for residential and light commercial applications where duty is not severe. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type GD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism (30-200 amp). 60/75 C conductor rating. TG3326R



Representative Image

#### Descriptors

Category	General Duty
----------	--------------

#### Specifications

Amperage	600 A
Poles	3
Wires	3
Fusing	Fusible
Enclosure	NEMA 3R (Outdoor)
Wire Range (Cu/Al)	(2) 4-500
240 Vac, NEC Std, 3-ph	75
240 Vac, Time Delay, 3-ph	100
GSA Compliance	Yes

#### Classifications

cUL Listed	Yes
UL Listed	Yes

#### Dimensions

Height	49.7
Depth	9.2
Width	22.8
Weight	124



