

AOD-N1





Ordering information

| Туре | Part no. |
|--------|----------|
| AOD-N1 | 6028961 |

Other models and accessories → www.sick.com/

Detailed technical data

Technical specifications

| reciffical specifications | |
|-------------------------------|---|
| Accessory family | Evaluation units |
| Additional function | Arithmetic calculations, Mean-value setting 1 \dots 4,096x, Frequency filters, automatic sensitivity adjustment |
| Connection type head A | Terminal board |
| Communication interface | Serial, RS-232 |
| Switching output | 5 x NPN (100 mA) ¹⁾ |
| Analog output | 2 x 4 mA 20 mA (≤ 300 Ω) ²⁾ |
| Housing material | Polycarbonat and nylon 66 |
| Operating voltage | DC 12 V (-5 %) DC 24 V (+10 %) |
| Power consumption | 6 W ³⁾ |
| Ambient operating temperature | -10 °C +45 °C |
| Enclosure rating | IP20 |
| Weight | 240 g |
| Description | OD Max evaluation unit, 5x NPN, required for OD350-x, OD85-x and OD30-x |

 $^{^{1)}}$ PNP: HIGH = V_S - (< 2 V) / LOW = < 2 V; NPN: HIGH = < 2 V / LOW = V_S.

Classifications

| eCl@ss 5.0 | 27270890 |
|--------------|----------|
| eCl@ss 5.1.4 | 27270890 |
| eCl@ss 6.0 | 27270890 |
| eCl@ss 6.2 | 27270890 |
| eCl@ss 7.0 | 27270890 |
| eCl@ss 8.0 | 27270890 |
| eCl@ss 8.1 | 27270890 |
| eCl@ss 9.0 | 27270892 |
| eCl@ss 10.0 | 27270892 |
| eCl@ss 11.0 | 27270892 |
| eCl@ss 12.0 | 27270992 |
| ETIM 5.0 | EC001825 |
| ETIM 6.0 | EC001825 |
| ETIM 7.0 | EC001825 |
| | |


 $^{^{2)}\,\}mathrm{Source}$ of analog output is either sensor heads, or calculation result.

 $^{^{\}rm 3)}$ When connected with two sensor heads, incl. analog current output.

| ETIM 8.0 | EC001825 |
|----------------|----------|
| UNSPSC 16.0901 | 41111613 |

Dimensional drawing (Dimensions in mm (inch))

AOD-xx AODG-xx




- ① DIN rail mounting
- ② LC display
- ③ Terminal board (detachable)
- ④ RS-232C interface
- ⑤ Sensor head B connection port
- Sensor head A connection port

Connection type

Connection diagram RS-232C




Terminal block connection type




Anschlussschema

Terminal block connection diagram




- ① Ground (0 V)
- ② Judgement Output = digital output
- 3 Alarm output
- 4 Analog output
- ⑤ Not assigned

Evaluation unit RS-232C



Adjustments

AOD-xx AODG-xx



⑦ Control elements

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

