9080GCB40

Circuit protector, Linergy, thermal magnetic overcurrent, track mount, 4.0A, 250VAC, 65VDC



Main

TTT CALL	
Range of Product	9080GCB
Product or Component Type	Circuit Protector
Trip Unit Type	Thermal-magnetic
Electrical Connection	Box lugs

Complementary

o o mpromornary		
Protection Type	Overcurrent	
Contact operation	Trip-free	
Device Application	Industrial Application	
Line Rated Current	4 A	
Number of Poles	1P	
Votlage Rating	250 V AC 65 V DC	
Wire Size	AWG 16AWG 10 copper	
Wire stripping length	0.5 in (12.70 mm)	
Terminal Tightening Torque	Control circuit 7 lbf.in (0.79 N.m) cage type connector	
Terminal Rating	Factory wiring only	
Operating Temperature	-22140 °F (-3060 °C)	
Calibration Temperature	70 °F (21 °C)	
Mounting Support	35 mm DIN rail 9080GH track	
Height	3.45 in (87.63 mm)	
Width	3.15 in (80.01 mm)	
Depth	0.5 in (12.70 mm)	

Environment

Product Certifications	UL recognized E233026 CCN QVNU2[RETURN]CE[RETURN]CSA file 025490 class 3211 07
Standards	DIN 57470 UL 1077 CSA C22.2 No 235

Ordering and shipping details

Category	21703-9080 GCB	
Discount Schedule	CP5	
GTIN	785901000938	
Returnability	Yes	
Country of origin	DE	

Packing Units

PCE	
1	
1.00 in (2.54 cm)	
3.30 in (8.382 cm)	
3.70 in (9.398 cm)	
2.56 oz (72.575 g)	
	1 1.00 in (2.54 cm) 3.30 in (8.382 cm) 3.70 in (9.398 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₽¥Yes

Contractual warranty

- Contraction was and		
Warranty	18 months	