

## Catalog Number: UPC Number: Status:

## GAA40BFE4AAFGAXX73 88861401880 Active

Abbreviated Switchgear, System Type 3 Phase/3 Wire, Bus Type Silver Plated with No Insluation, Main Bus Rating 4000A, Vertical Bus Rating 3,200A, Section Type Feeder, Short Circuit Rating 100kA, System Voltage 480V (508V Maximum), Compartment A Instrument Compartment, Compartment B Instrument Compartment, Compartment C E3 1200A Frame, Compartment D E3 1600A Frame, Enclosure Type Type 1, Door Option No Doors, Connection Options None, Section Depth 72 Inches, Section Width 30 Inches

## North American Specifications (UNSPSC)

North American Specifications (UNSF 3C)	
39121116 Low voltage switchgear	
4374 Low voltage switchgear	
ABB	
Emax Link	
Barriers between the bus compartment and the ca-	
ble compartment for increased personnel protection	
4000A	
100kA	
92 Inches x 72 Inches x 30 Inches	
No Insulation	
Туре 1	
3	
1	
72x30x92	

Weight Uom

2134 lbs. Each

## For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com