

Load:Logic®
Control Panels
8 - Relay



Features

- Compact single enclosure allows for 4 or 8 Relays
- All inputs are configurable to low voltage input devices including switches, occupancy sensors, and photocells
- LCD user interface utilizes easy to follow intuitive configuring tools

Ordering Information

Description	UPC Number	Catalog Number
Control Panel, 8 field installed Relay, Master	78358542723	CP082RRR1

Listings


UL916, ASHRAE 90.1, IEEC, California Title 24 (CEC), cUL, LEED Compliant

Specifications

Body	Steel, powder coated after fabrication
Physical	NEMA 1 Surface Enclosure w/ hinged locking door
Physical	Total of 14 (7 Top and 7 Bottom) 1" KO's
Dimensions	17" H x 14.5" W x 4" D

Performance

Electrical	
Configuration	Master Control Panel
Number of Relay Spaces	8
Power Supply	120-277V AC
Environmental	
Operating Location	Indoor Use Only
Operating Temperature	0° tp 50°C (32° to 112°F) Relative Humidity (non-condensing) 10% to 90%



Complementary Products

20A, Single Pole, Electrically Held, Normally Open Relay	R21HN
30A, Single Pole, Latching Relay	R31LX
20A, 2-Pole, Electrically Held, Normally Open Relay	R202HN
20A, 2-Pole, Electrically Held, Normally Closed Relay	R202HC
8-Channel dimming controller option board	CPDM8CTRB

Online Resources

eCatalog

