



## Main

Product	Surge protection device
Range	Surgelogic
Device Short Name	IMA

## Complementary

Voltage Rating	480 V delta AC
MCOV	550 V
SCCR	200 kA
Surge Current	120 kA per phase
Nominal Discharge Current	20 kA
Number of Phases	3 phase
Wiring Configuration	3-wire
Connection	Lugs AWG 12...AWG 2 aluminium/copper 35.40 lbf.in (4 N.m)
Provided Equipment	Alarm enable/disable switch Diagnostic display Backplane Cables
Height	6.13 in (155.7 mm)
Width	9.86 in (250.4 mm)
Depth	3.65 in (92.7 mm)

## Environment

Enclosure Rating	NEMA 1
Standards	UL 1449:ed. 4 CSA C22.2 No 8:1986 UL 96A:ed. 12 UL 1283 IEC 61643-1

## Ordering and shipping details

Category	08468-SURGE PROTECTION OEM
Discount Schedule	DE1B
GTIN	3606486149089
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.14 in (15.6 cm)
Package 1 Width	9.84 in (25.0 cm)
Package 1 Length	3.66 in (9.3 cm)
Package 1 Weight	8.40 lb(US) (3.81 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>