

## Product data sheet

### Characteristics

# HVL515DEWR1H

Switchgear, HVL, duplex, 600A, 15kV, 10 to 100E current limit fuse, transformer disconnect, right, NEMA 3R



### Main

Product	Transformer Disconnect
Not Included	Fuse to be ordered separately
Device application	Transformer right side

### Complementary

Protection type	Fuse current limiter
Associated fuse rating	10 A E 15 A E 20 A E 25 A E 30 A E 40 A E 50 A E 65 A E 80 A E 100 A E
Line Rated Current	600 A
Momentary Amperes Asymmetrical	40 kA
Full Load Current	300 A
Frequency	50/60 Hz
Number of Poles	3P
[Ur] highest voltage for equipment	15 kV
Basic Insulation Level	95 kV
Enclosure Rating	NEMA 3R
Electrical Connection	Lugs
Wire Gauge	AWG 2...600 kcmil aluminium/copper
Enclosure Width	76 in (1930.40 mm)
Enclosure Depth	60 in (1524.00 mm)
Enclosure Height	97 in (2463.80 mm)

### Environment

Product Certifications	UL Listed[RETURN]cUL
------------------------	----------------------

### Ordering and shipping details

Category	07945-15KV DIGEST HVL NEMA 3R
Discount Schedule	PE5A
GTIN	3606486276747
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2800.00 lb(US) (1270.059 kg)

Contractual warranty

Warranty	18 months
----------	-----------