

Catalog Number: GBA40BFE4AAFEAXX73
UPC Number: 88861406662
Status: Active

Abbreviated Switchgear, System Type 3 Phase/4 Wire, Bus Type Silver Plated with No Insulation, Main Bus Rating 4000A, Vertical Bus Rating 3,200A, Section Type Feeder, Short Circuit Rating 100kA, System Voltage 480V (508V Maximum), Compartment A Instrument Compartment, Compartment B Instrument Compartment, Compartment C E3 1200A Frame, Compartment D E3 800A Frame, Enclosure Type Type 1, Door Option No Doors, Connection Options None, Section Depth 72 Inches, Section Width 30 Inches

North American Specifications (UNSPSC)

UNSPSC	39121116 Low voltage switchgear
IGCC	4374 Low voltage switchgear
Brand Name	ABB
Type	Emax Link
Special Features	Barriers between the bus compartment and the cable compartment for increased personnel protection
Bus Rating	4000A
Short Circuit Rating	100kA
Size	92 Inches x 72 Inches x 30 Inches
Insulation	No Insulation
Enclosure	Type 1
Phase	3

Packaging

Outer Quantity	1
Outer Dimensions (inches)	72x30x92
Weight Uom	2134 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com