

Rittal – The System.

Faster – better – everywhere.

► Network/server enclosures TS IT with glazed door, IP 55, empty enclosure – DK 5510.790

Date : Jan 19, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Network/server enclosures TS IT with glazed door, IP 55, empty enclosure – DK 5510.790

created: 19.01.2017 build on www.rittal.com/us-en



Product description

Material: Carbon steel
Aluminum

Surface finish: Enclosure frame: Dipcoat-primed
Interior installation: Dipcoat-primed
Doors and roof: Dipcoat-primed, powder coated

Color: Housing frame and panels: RAL 7035

Protection category IP to IEC 60 529: IP 55 only in conjunction with baying seal or screw-fastened side panels

Supply includes: Enclosure frame TS 8 with doors and roof plate
Glazed aluminum door, front (180°)
Carbon steel door at the rear, 180° hinges
Lock front and rear: Comfort handle for semi-cylinders and security lock 3524 E
Roof plate, one-piece, solid
Base tray and base plate, multi-piece, solid
Baying seal and sealing kit for base plates (supplied loose)
Connection accessories for potential equalization with earthing point (supplied loose)
IPPC pallet

Note: Door opening may vary depending on site requirements or applications.
for enclosures with height and depth: 2000 x 1200 mm / 2200 x 1000 mm / 2200 x 1200 mm,
the matching side panels are optionally available and are supplied fitted to the enclosure

Base material: Carbon steel

Product features

Dimensions: Height: 2000 mm (79 ")
Width: 600 mm (24 ")
Depth: 1200 mm (47 ")

Packaging unit: 1 pc(s).

EAN: 4028177703162

Customs tariff number: 94032080

ETIM 6.0: EC002499

ETIM 5.0: EC002499

eCl@ss 8.0/8.1: 27180207

eCl@ss 7.0/7.1: 27180207

eCl@ss 6.0/6.1: 27180207

eCl@ss 5.1/5.1.4: 27180201

Approvals

Approvals: UL + C-UL

Certificates: Protection category