

Catalog Number: UPC Number: Status:

GAA40XAE4AAAAAXX74 88861401897 Active

Abbreviated Switchgear, System Type 3 Phase/3 Wire, Bus Type Silver Plated with No Insluation, Main Bus Rating 4000A, Vertical Bus Rating No Bus Provided, Section Type Auxiliary, Short Circuit Rating 100kA, System Voltage 480V (508V Maximum), Compartment A Instrument Compartment, Compartment B Instrument Compartment, Compartment C Instrument Compartment, Compartment D Instrument Compartment, Enclosure Type Type 1, Door Option No Doors, Connection Options None, Section Depth 72 Inches, Section Width 40 Inches

North American Specifications (UNSPSC)

	- (/
UNSPSC	39121116 Low voltage switchgear
IGCC	4374 Low voltage switchgear
Brand Name	ABB
Туре	Emax Link
Special Features	Barriers between the bus compartment and the ca-
	ble compartment for increased personnel protection
Bus Rating	4000A
Short Circuit Rating	100kA
Size	92 Inches x 72 Inches x 40 Inches
Insulation	No Insulation
Enclosure	Туре 1
Phase	3

Packaging

Outer Quantity	1
Outer Dimensions (inches)	72x40x92
Weight Uom	1740 lbs. Each

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com