

9422BTCN30

Operating mechanism, flange mounted, fixed depth assembly, 30A, 600 V, no fuse, switch mechanism, 6 inch handle



Main	
Range	9422T
Product	Disconnect Switch
Disconnect Type	Non-fusible disconnect switch

Complementary	
Mounting Type	Bracket fixed depth
Current Rating	30 A
Horsepower Rating	7.5 Hp 200 V AC 7.5 Hp 230 V AC 15 Hp 460 V AC 20 Hp 575 V AC 5 hp 250 V DC
Handle Type	6 in handle included

Environment	
Certifications	UL Recognized[RETURN]CSA

Ordering and shipping details	
Category	21732-9422
Discount Schedule	CP1
GTIN	785901872290
Returnability	No
Country of origin	MX

Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.20 in (33.528 cm)
Package 1 Width	8.40 in (21.336 cm)
Package 1 Length	12.20 in (30.988 cm)
Package 1 Weight	9.64 lb(US) (4.373 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------