



Representative Image

Catalog No. 9T10A1001G31

Description: "3A,15KVA,480-208Y,115C,N2,K1,DOE"

UPC No 783173904350

Home > Transformers > Dry Type Vented > General Purpose

ABB's Low Voltage Dry Type transformers are built to last and are designed with exclusive features. With easy installation and all of the specifications you trust, it's easy to see why ABB QL dry type transformers are preferred by contractors. Our Type QL transformers meet DOE efficiency standards. They are available with aluminum or copper windings and in all three temperature rise ratings.

Descriptors

Category	General Purpose
GO Schedule	TY

Specifications

TransType	DOE 2016
Phase	3
PriVoltage	480
SecVoltage	208Y/120
KVA	15.0 KVA
Coil Material	AL
TempRise	115.0 °C
Frequency	60 Hz
Impedance	3.4 %
AmbTemp	40.0 °C
EnergyEfficiency	DOE 2016
KFactor	K1
Enclosure Type	NEMA 2
Sound	Std

Classifications

CE	0
----	---

Publications

Title	Publication No.	Publication Type
QL Dry Type Transformers Rev. G	DEA-492	Brochures

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.