QO120VH1021

Mini circuit breaker, QO, 20A, 1 pole, 120/240VAC, 22kA, plug in mount, AC shunt





Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	20 A
Voltage Rating	120/240 V AC
	240 V AC
	120 V AC
Mounting Type	Plug-in
Number of Poles	1P
Circuit Breaker Type	Standard
Ratings	HACR and Switching Duty rated
Electrical Connection	Pressure plate
Options	Shunt trip 120/208/240 V AC

Complementary

22 KA 120/240 V AC 50/60 Hz 22 KA 240 V AC 50/60 Hz 22 kA 120 V AC 50/60 Hz	
2	
AWG 14AWG 8 copper or aluminium	
40.71 lbf.in (4.6 N.m)	
2.99 in (76 mm)	
1.50 in (38 mm)	
2.91 in (74 mm)	
0.66 lb(US) (0.299 kg)	
	22 KA 240 V AC 50/60 Hz 22 kA 120 V AC 50/60 Hz 2 AWG 14AWG 8 copper or aluminium 40.71 lbf.in (4.6 N.m) 2.99 in (76 mm) 1.50 in (38 mm) 2.91 in (74 mm)

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	00926-QO IND SPECIALTY CB
Discount Schedule	DE2A
GTIN	785901166108
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.20 in (8.128 cm)
Package 1 Width	3.50 in (8.89 cm)
Package 1 Length	4.60 in (11.684 cm)
Package 1 Weight	10.56 oz (299.371 g)

Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

18 months