

Rittal – The System.

Faster – better – everywhere.

Compact enclosures AE – AE 1213.500

Date : Jan 19, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Compact enclosures AE – AE 1213.500

created: 19.01.2017 build on www.rittal.com/us-en



Product description

Material:	Housing: Carbon steel Door: Carbon steel, all-round foamed-in PU seal
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 12
IK code:	IK08
Supply includes:	Housing with hinged door(s), of all-round solid construction Flange (gland) plate(s) in enclosure base Mounting plate Lock: 3 mm double-bit 3-point locking system
Base material:	Carbon steel

Product features

Dimensions:	Height: 1200 mm (47 ") Width: 1000 mm (39 ") Depth: 300 mm (12 ")
Material thickness:	Housing: 1.5 mm (0.06 ")

Door: 2 mm (0.08 ")
Mounting plate: 3 mm (0.12 ")

Mounting plate:	Height: 1155 mm (45 ") Width: 940 mm (37 ")
Number of doors:	2
Lock version:	3-point locking system
No. of locks:	1
Lock Insert:	3 mm double-bit
Flange plate, size:	4
Flange plate, qty:	2
Packaging unit:	1 pc(s).
Weight/packaging unit:	85 kg
EAN:	4028177252431
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180102

Approvals

Approvals:	Bureau Veritas CSA DNV GL Lloyds Register of Shipping Russian Maritime Register of Shipping TÜV UL + C-UL
Certificates:	EAC IK-Code

Protection category

Declarations:

Declaration of conformity

2017 © Rittal Corporation