



Representative

Catalog Number: S201PR-K40
UPC Number: 80432563686
Status: Active

Miniature Circuit Breaker with Ring Cable Lug, Branch Circuit Protection, Rated Current 40 Amps, 1 Pole, Interrupt Rating 10 kA, Thermal Magnetic Trip Curve K, Voltage up to 240 VAC, DIN Rail Mounted, Finger Safe and Multi-Function Terminals, UL 489, CSA 22.2 No. 5

North American Specifications (UNSPSC)

UNSPSC	39121603 Miniature circuit breakers
IGCC	4897 Miniature circuit breakers
Brand Name	ABB
Type	High Performance MCB, Branch Circuit Protection
Special Features	DIN Rail Mounting, Finger Safe and Multi-Function Terminals
Application	Designed for Allowing Higher In-Rush Current During System Start Up; Example: Motors, Transformers
Standard	UL 489, CSA 22.2 No. 5, IEC 60947-2, UL E212323
Voltage Rating	240 VAC
Amperage Rating	40 Amps
Frequency Rating	50/60 Hertz
Trip Type	K
Interrupt Rating	10 kA
Number Of Poles	1
Auxiliary Contacts	Yes
Length	69 mm
Width	17.5 mm
Height	100 mm
Operating Temperature	-25 to +55 Degrees Celcius

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	26 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com