

Han B Top Entry LC M20 Exi_For Single Le



-	
Part number	19 36 010 1440
Specification	Han B Top Entry LC M20 Exi_For Single Le
HARTING eCatalogue	https://b2b.harting.com/19360101440

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] Ex
Type of hood/housing	Hood

Version

Locking type	Single locking lever
Size	10 B
Version	Top entry
Cable entry	1x M20
Field of application	Connectors for explosion hazardous environments
Details	ATTENTION! Only to be used with Han [®] Ex inserts!

Technical characteristics

Limiting temperature	-20 +40 °C
Degree of protection acc. to IEC 60529	IP65 With cable gland
Material properties	

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 5015 (sky blue)
RoHS	compliant
ELV status	compliant
China RoHS	e

Page 1 / 2 | Creation date 2020-03-18 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties

REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No
Commercial data	
Commercial data	
Packaging size	1
Net weight	310 g
Country of origin	China
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors