

Catalog Number: UPC Number: Status:

GAA10CFE4AEGFAXX83 88861402208 Active

Abbreviated Switchgear, System Type 3 Phase/3 Wire, Bus Type Silver Plated with No Insluation, Main Bus Rating 10000A, Vertical Bus Rating 4,000A, Section Type Feeder, Short Circuit Rating 100kA, System Voltage 480V (508V Maximum), Compartment A Instrument Compartment, Compartment B E3 800A Frame, Compartment C E3 1600A Frame, Compartment D E3 1200A Frame, Enclosure Type Type 1, Door Option No Doors, Connection Options None, Section Depth 84 Inches, Section Width 30 Inches

North American Specifications (UNSPSC)

North American Specifications (UNSF 3C)	
UNSPSC	39121116 Low voltage switchgear
IGCC	4374 Low voltage switchgear
Brand Name	ABB
Туре	Emax Link
Special Features	Barriers between the bus compartment and the ca-
	ble compartment for increased personnel protection
Bus Rating	10000A
Short Circuit Rating	100kA
Size	92 Inches x 84 Inches x 30 Inches
Insulation	No Insulation
Enclosure	Type 1
Phase	3
Packaging	
Outer Quantity	1
Outer Dimensions (inches)	84x30x92

Weight Uom

2663 lbs. Each

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com