

8736SGO1V02S

NEMA Starter, Type S, reversing, vertical, Size 5, 270A, 200 HP at 575 VAC, 10 kA SCCR, 3 phase, 3 pole, melting alloy overload, 120 VAC coil, open



Main

Product Type	Starter
Product Range	S
Starter Type	Reversing

Complementary

NEMA Size	5
Rated Current	270 A
Number of Poles	3P
Mounting Orientation	Vertical
Wiring Mode	3 wires
Maximum Voltage Rating	600 V AC
Phase	3 phase
Type of Overload	Melting alloy 3
Horsepower Rating	75 HP 200 V AC 100 HP 230 V AC 200 HP 460 V AC 200 HP 575 V AC
SCCR	Circuit-breaker: 10 kA at 600 V AC Fuse: 10 kA at 600 V AC
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control Circuit Type	Separate control circuit
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Terminal Type	Screw clamp terminals
Height	39.16 in (994.66 mm)
Width	10.75 in (273.05 mm)
Depth	9.38 in (238.25 mm)

Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed[RETURN]CSA


## Ordering and shipping details

Category	21274-8702,36SG(NOT S*R,S*T,S*W)
Discount Schedule	CP1
GTIN	785901865469
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	31.26 in (79.4 cm)
Package 1 Width	103.03 in (261.7 cm)
Package 1 Length	57.17 in (145.2 cm)
Package 1 Weight	92.64 lb(US) (42.019 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------