## Rittal - The System.

Faster – better – everywhere.

## CM Compact System Enclosures – CM 5113.500

Date : Jan 19, 2017



NCLOSURES >> POWER DISTRIBUTION >> CLIMATE CONTROL >> IT INFRASTRUCTURE >> SOFTWARE & SERVICES >>

## **CM Compact System Enclosures – CM 5113.500**

created: 19.01.2017 build on www.rittal.com/us-en



Droduct	description
riouuci	description

Material: Housing: Carbon steel, 1.5 mm

Door: Carbon steel, 2.0 mm, all-round foamed-in PU seal

Mounting plate: Carbon steel, 3.0 mm

Surface finish: Housing and door: Dipcoat primed, powder-coated on the outside, textured paint

Mounting plate: Zinc-plated

Color: RAL 7035

Protection category IP to IEC 60 529:

IP 55 with selection of the appropriate base plate or trim panel

Protection category NEMA:

NEMA 12 with selection of the appropriate base plate or trim panel

IK code:

IK08

Supply includes:

Housing with hinged door(s)

3-point locking system with double-bit insert

Mounting plate

Open base for individual cable entry

Base material: Carbon steel

## **Product features**

**Dimensions:** Height: 1200 mm (47 ")

Width: 600 mm (24 ") Depth: 400 mm (16 ")

Mounting plate: Height: 1155 mm (45 ")

© Rittal 2017

Number of doors:	1
Door catch on right, may be swapped to the left:	yes
Packaging unit:	1 pc(s).
Weight/packaging unit:	56 kg (123.5 lb.)
EAN:	4028177479715
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
e CI@ss 8.0/8.1:	27180101
e Cl@ss 7.0/7.1:	27180101
e Cl@ss 6.0/6.1:	27180101
e Cl@ss 5.1/5.1.4:	27180102
Approvals	
Approvals:	CSA Lloyds Register of Shipping TÜV UL + C-UL
Certificates:	IK-Code
Declarations:	Declaration of conformity

2017 © Rittal Corporation

© Rittal 2017 2