



Representative

Catalog Number: **CPC16/50M**
Product ID: 7TCA298000R0007
EAN Number: 05020963053320
Status: Active

Flame Retardant, Highly Flexible Conduit, NC Size 16/NW Size 13, Outside Diameter 16.0mm, Inside Diameter 11.0mm, Static Bend Radius 30mm, Very High UV Resistance and Fatigue Life, IP40 Rating, FR Co-Polyester, Reel Length 50 Meters, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5540 Flexible Non-Metallic Conduit
Brand Name	Harnessflex
Type	Flame Retardant Conduit
Application	Ideal for Harness Applications Such as Engine, Body Section and Chassis. CPC is Resistant to Hydrocarbons, Greases, Fuels and Oils
Standard	RoHS, Conforms with end of life vehicle directive (ELV)EU200/53/EC
Trade Size	NC16/NW13
Outside Diameter	16.0mm
Inside Diameter	11.0mm
Length	50 m
Radius	Static Bend Radius 30mm
Flexibility	Very High
Material	Fire Resistant Co-Polyester
Color	Black

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	16mm
Nominal size in inch	3/8 inch
Outer diameter	16mm
Inner diameter	11mm
Material	Other
Operating temperature	-50-+130°C
Degree of protection (IP)	IP40
Fire resistance in accordance with UL94	V2
UV resistant	Y
Colour	Black
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	N
Halogen free	Y

Packaging

Inner Quantity	1
Inner Dimensions (inches)	17x17x6
Outer Quantity	1
Outer Dimensions (inches)	17x17x6
Weight Uom	5.84 lbs. Each

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com