9080GM6

Terminal block, Linergy, box lug connector, natural colored block, 30A, 600V



Main	
Range of Product	9080G
Product Type	Terminal block
Localisation on Device	Standard
Color	Natural
Quantity	Set of 50

Complementary

Complementary		
Voltage Rating	600 V AC/DC	
Current Rating	30 A UL 30 A CSA	
Wire Size	AWG 22AWG 10 copper	
Mounting Type	9080GH track 35 mm DIN rail	
Certifications	CE[RETURN]CSA file 62144 class 6228 01[RETURN]UL recognized E60616 CCN XCFR2	
Protection Type	Fingersafe DIN 57470	
Electrical Connection	Zinc plated steel box lugs	
Material	Nylon: block Tin plated brass: busbar	
Ambient Air Temperature for Operation	-40257 °F (-40125 °C)	
Electrical Connrection Tightening Torque	Lug zinc plated steel 78 lbf.in (0.790.90 N.m) : AWG 22AWG 10 copper)	
Height	1.82 in (46.23 mm)	
Width	1.72 in (43.69 mm)	
Depth	0.235 in (5.97 mm)	
Density	51 per foot	
Compatible End Barrier	GM6B	

Ordering and shipping details

3 1 - 1	
Category	21702-9080 G (NOT GCB)
Discount Schedule	CP5
GTIN	785901743927
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	0.20 in (0.508 cm)	
Package 1 Width	1.70 in (4.318 cm)	
Package 1 Length	1.70 in (4.318 cm)	
Package 1 Weight	0.28 oz (8.0 g)	
Unit Type of Package 2	CAR	

Number of Units in Package 2	500
Package 2 Height	6.00 in (15.24 cm)
Package 2 Width	12.50 in (31.75 cm)
Package 2 Length	16.00 in (40.64 cm)
Package 2 Weight	9.47 lb(US) (4.294 kg)
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancel and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₽¥Yes
PVC free	Yes

Contractual warranty

Warranty	18 months