QOB3201042

Mini circuit breaker, QO, 20A, 3 pole, 120/240VAC, 10kA, bolt on mount, AC/DC shunt





Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	20 A
Voltage Rating	120/240 V AC 240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	3P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Pressure plate
Options	Shunt trip 12/24 V AC/DC

Complementary

Interrupt Rating	10 KA 120/240 V AC 50/60 Hz	_
	10 KA 240 V AC 50/60 Hz	
	10 kA 120 V AC 50/60 Hz	
Number of Panel Spaces	4	
Wire Size	AWG 14AWG 8 copper or aluminium	
Tightening Torque	35.40 lbf.in (4 N.m)	
Height	2.99 in (76 mm)	
Width	2.99 in (76 mm)	
Depth	2.91 in (74 mm)	
Net Weight	1.21 lb(US) (0.549 kg)	

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	00015-QOB CIRCUIT BREAKERS
Discount Schedule	DE2
GTIN	785901528890
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.10 in (7.874 cm)	
Package 1 Width	3.50 in (8.89 cm)	
Package 1 Length	4.60 in (11.684 cm)	
Package 1 Weight	19.36 oz (548.847 g)	

Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

18 months