



Representative

Catalog Number: S203-D40NA
UPC Number: 88861419085
EAN Number: 04016779532914
Status: Active

Miniature Circuit Breaker, Supplementary Protector, Rated Current 40 Amps, 3 Plus Neutral Pole, Interrupt Rating 6 kA, Thermal Magnetic Trip Curve D, Voltage up to 277/Y480 VAC, DIN Rail Mounted, Finger Safe and Multi-Function Terminals, UL 1077, CSA 22.2 No. 235

North American Specifications (UNSPSC)

UNSPSC	39121603 Miniature circuit breakers
IGCC	4897 Miniature circuit breakers
Brand Name	ABB
Type	High Performance MCB Provides Compact Supplementary, Energy Limiting, Circuit Protection
Special Features	DIN Rail Mounting, Finger Safe and Multi-Function Terminals
Application	Designed for Allowing Higher In-Rush Current During System Start Up; Example: Motors, Transformers
Standard	UL 1077, CSA 22.2 No. 235, IEC 60898
Voltage Rating	277/Y480 VAC
Amperage Rating	40 Amps
Frequency Rating	50/60 Hertz
Trip Type	D
Interrupt Rating	6 kA
Number Of Poles	3 Plus Neutral
Auxiliary Contacts	Yes
Length	69 mm
Width	52.5 mm
Height	88 mm
Operating Temperature	-25 to +55 Degrees Celcius

Packaging

Outer Quantity	1
Outer Dimensions (inches)	3.071x3.622x3.15
Weight Uom	1.16 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com